

# SAFETY DATA SHEET

## Product Name ENGINE FLUSH

### 1. IDENTIFICATION OF THE MATERIAL AND SUPPLIER

Supplier Name REVENG GLOBAL AUTOMOTIVE TECHNOLOGY Address PO BOX 202, CAMDEN, NSW, 2570, AUSTRALIA

Emergency 000

0419488895

Web Site www.reveng.net.au

Synonym(s) EF- REF350

Use(s) ENGINE FLUSH
SDS Date 1ST AUGUST 2019

### 1. HAZARDS IDENTIFICATION

NOT CLASSIFIED AS HAZARDOUS ACCORDING TO ASCC CRITERIA

NOT CLASSIFIED AS A DANGEROUS GOOD BY THE CRITERIA OF THE ADG CODE

UN No. None Allocated DG Class None Allocated Subsidiary Risk(s) None Allocated Packing Group None Allocated Hazchem Code None Allocated EPG None Allocated

## 2. COMPOSITION/INFORMATION ON INGREDIENTS

| Ingredient    | Formula       | CAS No.       | Content       |
|---------------|---------------|---------------|---------------|
| DISPERSANTS   | Not Available | Not Available | Not Available |
| LUBRICANTS    | Not Available | Not Available | Not Available |
| SURFACTANT(S) | Not Available | Not Available | Not Available |

## 3. FIRST AID MEASURES

Eye If in eyes, hold eyelids apart and flush the eye continuously with running water. Continue flushing until advised to

stop by the Poisons Information Centre or a doctor, or for at least 15 minutes.

**Inhalation** If inhaled, remove from contaminated area. Apply artificial respiration if not breathing.

**Skin** If skin or hair contact occurs, remove contaminated clothing and flush skin and hair with running water. Continue

flushing with water until advised to stop by the Poisons Information Centre or a doctor.

**Ingestion** For advice, contact a Poisons Information Centre on 13 11 26 (Australia Wide) or a doctor (at once). If swallowed,

do not induce vomiting.

Advice to Doctor Treat symptomatically

## 4. FIRE FIGHTING MEASURES

Flammability Combustible. May evolve toxic gases (carbon oxides, hydrocarbons) when heated to decomposition.

**Fire and**Evacuate area and contact emergency services. Toxic gases may be evolved in a fire situation. Remain upwind and notify those downwind of hazard. Wear full protective equipment including Self Contained Breathing Apparatus (SCBA) when combating fire. Use waterfog to cool intact containers and nearby storage areas.

December of the idea of the control of the income of the i

**Extinguishing** Dry agent, carbon dioxide or foam. Prevent contamination of drains or waterways.

## Product Name ENGINE FLUSH

Hazchem Code None Allocated

### 6. ACCIDENTAL RELEASE MEASURES

**Spillage** 

Use personal protective equipment. Clear area of all unprotected personnel. Ventilate area where possible. Contain spillage, then cover / absorb spill with non-combustible absorbant material (vermiculite, sand, or similar), collect and place in suitable containers for disposal.

## 7. STORAGE AND HANDLING

Storage Store in a cool, dry, well ventilated area, removed from oxidising agents, acids, alkalis, heat or ignition sources

and foodstuffs. Ensure containers are adequately labelled, protected from physical damage and sealed when not in use. Check regularly for leaks or spills. Large storage areas should have appropriate fire protection systems. Store

as a Class C1 Combustible Liquid (AS1940).

**Handling** Before use carefully read the product label. Use of safe work practices are recommended to avoid eye or skin

contact and inhalation. Observe good personal hygiene, including washing hands before eating. Prohibit eating,

drinking and smoking in contaminated areas.

## 8. EXPOSURE CONTROLS/ PERSONAL PROTECTION

**Exposure Stds** No exposure standard(s) allocated.

Biological Limits No biological limit allocated.

Engineering Controls

**PPE** 

Avoid inhalation. Use in well ventilated areas. Where an inhalation risk exists, mechanical extraction ventilation is

recommended. Maintain vapour levels below the recommended exposure standard.

Wear splash-proof goggles and rubber or PVC gloves. When using large quantities or where heavy contamination is likely, wear: coveralls. Where an inhalation risk exists, wear: a Type A (Organic vapour) respirator. With prolonged use, wear: nitrile or viton (R) gloves and coveralls.





### 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance CLEAR AMBER COLOURED LIQUID Solubility (Water) IN SOLUBLE

Odour HYDROCARBON Specific Gravity 0.9 (Approximately)

**pH** N/A **% Volatiles** < 20 %

Vapour Pressure NOT AVAILABLE Flammability CLASS C1 COMBUSTIBLE

Vapour Density NOT AVAILABLE Flash Point > 70°C

Boiling PointNOT AVAILABLEUpper Explosion LimitNOT AVAILABLEMelting PointNOT AVAILABLELower Explosion LimitNOT AVAILABLE

## 10. STABILITY AND REACTIVITY

**Chemical Stability** Stable under recommended conditions of storage.

**Conditions to Avoid** Avoid heat, sparks, open flames and other ignition sources.

Material to Avoid Incompatible with oxidising agents (eg. hypochlorites), acids (eg. nitric acid), alkalis (eg. hydroxides), heat

and ignition sources.

**Decomposition** May evolve toxic gases (carbon oxides, hydrocarbons) when heated to decomposition.

**Hazardous Reactions** Polymerization is not expected to occur.

## Product Name ENGINE FLUSH

### 11. TOXICOLOGICAL INFORMATION

**Health Hazard** Use safe work practices to avoid eye or skin contact and inhalation. The mineral oil contained within this product is

**Summary** highly refined and therefore is not classifiable as to its carcinogenicity in humans (IARC Group 3).

**Eye** Contact may result in irritation, lacrimation, pain and redness.

Inhalation Over exposure may result in irritation of the nose and throat, with coughing.

Skin Prolonged or repeated contact may result in mild irritation, rash and dermatitis.

Ingestion Ingestion of large quantities may result in nausea, vomiting, abdominal pain, diarrhoea, and drowsiness.

Aspiration may result in chemical pneumonitis and pulmonary oedema.

**Toxicity Data** No LD50 data available for this product.

### 12. ECOLOGICAL INFORMATION

**Environment** Mineral oils biodegrade slowly and should not be released to waterways or soil. They can float on water,

restricting oxygen exchange with possible asphyxiation of aquatic life.

**Ecotoxicity** Not classified as dangerous to the aquatic environment.

Persistence / Degradability

Expected to be inherently biodegradable.

Mobility Low solubility and is expected to migrate from water to the land. Expected to partition to sediment and

wastewater solids.

### 13. DISPOSAL CONSIDERATIONS

Waste Disposal Reuse where possible or return to manufacturer/supplier. May be recycled. Do not release to drains or waterways.

Contact the manufacturer for additional information.

**Legislation** Dispose of in accordance with relevant local legislation.

### 14. TRANSPORT INFORMATION

### NOT CLASSIFIED AS A DANGEROUS GOOD BY THE CRITERIA OF THE ADG CODE

Shipping Name None Allocated

UN No. None Allocated DG Class None Allocated Subsidiary Risk(s) None Allocated Packing Group None Allocated Hazchem Code None Allocated EPG None Allocated

### 15. REGULATORY INFORMATION

**Poison Schedule** A poison schedule number has not been allocated to this product using the criteria in the Standard for the Uniform Scheduling of Drugs and Poisons (SUSDP).

AICS All chemicals listed on the Australian Inventory of Chemical Substances (AICS).

### 16. OTHER INFORMATION

Additional\_ Information MINERAL OILS - SOLVENT REFINED; Animal experiments and human experience have not shown cancer risks when handling solvent refined mineral oils, unlike non refined mineral oils. CLEANING MINERAL OIL CONTAMINATED CLOTHING; Cleaners are advised that when cleaning oil contaminated clothing it is essential that freshly distilled solvent is used for each batch, including final rinse, as even filtered solvent will leave oil residues.

MINERAL OILS - USED; Used mineral oils in engine crankcases and other high temperature/high stress environments may contain potentially harmful residues, some of which have been shown to cause irreversible skin effects, including cancer. Prolonged and repeated inhalation of mists associated with used mineral oils may result in pulmonary fibrosis.

MINERAL OILS - INJECTION; Where high pressure applications are used the risk of accidental injection under the skin exists and may result in an extremely painful and serious injury requiring immediate medical attention. Depending on the pressure used, mineral oils may be injected a considerable distance below the skin and may cause permanent tissue damage. SEEK IMMEDIATE MEDICAL ATTENTION. EXERCISE EXTREME CARE WHEN USING HIGH PRESSURE EQUIPMENT.

ABBREVIATIONS:

ADB - Air-Dry Basis.

BEI - Biological Exposure Indice(s)

CAS# - Chemical Abstract Service number - used to uniquely identify chemical compounds.

## Product Name ENGINE FLUSH

CNS - Central Nervous System.

EINECS - European INventory of Existing Commercial chemical Substances.

IARC - International Agency for Research on Cancer.

M - moles per litre, a unit of concentration.

mg/m3 - Milligrams per cubic metre.

NOS - Not Otherwise Specified.

NTP - National Toxicology Program.

OSHA - Occupational Safety and Health Administration.

pH - relates to hydrogen ion concentration using a scale of 0 (high acidic) to 14 (highly alkaline).

ppm - Parts Per Million.

RTECS - Registry of Toxic Effects of Chemical Substances.

TWA/ES - Time Weighted Average or Exposure Standard.

### HEALTH EFFECTS FROM EXPOSURE:

It should be noted that the effects from exposure to this product will depend on several factors including: frequency and duration of use; quantity used; effectiveness of control measures; protective equipment used and method of application. Given that it is impractical to prepare a Chem Alert report which would encompass all possible scenarios, it is anticipated that users will assess the risks and apply control methods where appropriate.

#### PERSONAL PROTECTIVE EQUIPMENT GUIDELINES:

The recommendation for protective equipment contained within this Chem Alert report is provided as a guide only. Factors such as method of application, working environment, quantity used, product concentration and the availability of engineering controls should be considered before final selection of personal protective equipment is made.

### **Report Status**

This document has been compiled by RMT on behalf of the manufacturer of the product and serves as the manufacturer's Safety Data Sheet ('SDS').

It is based on information concerning the product which has been provided to RMT by the manufacturer or obtained from third party sources and is believed to represent the current state of knowledge as to the appropriate safety and handling precautions for the product at the time of issue. Further clarification regarding any aspect of the product should be obtained directly from the manufacturer.

While RMT has taken all due care to include accurate and up-to-date information in this SDS, it does not provide any warranty as to accuracy or completeness. As far as lawfully possible, RMT accepts no liability for any loss, injury or damage (including consequential loss) which may be suffered or incurred by any person as a consequence of their reliance on the information contained in this SDS.

SDS Date: 1<sup>ST</sup> AUGUST 2019 End of Report